



ESD-SAFE LABELS



POLYONICS[®]

Personal Chemistry

**PROTECTION FOR YOUR
ESD SENSITIVE COMPONENTS**

POLYONICS ESD-SAFE LABEL PRODUCT LINE

Film	Product	Finish	Adhesive	Static Dissipative	Low Charging	Temperature	Reach and RoHS Compliant	UL 969 Recognized
1 mil (25 µm) Polyimide	XF-781	Semi-gloss White	1 mil (25 µm) Acrylic	✓	✓	100 hrs at 302 °F (150°C)	✓	✓
	XF-784	Matte White	1 mil (25 µm) Acrylic	✓	✓	5 min at 500 °F (260 °C)	✓	✓
2 mil (50 µm) Polyimide	XF-782	Semi-gloss White	2 mil (50 µm) Acrylic	✓	✓	90 sec at 572 °F (300 °C)	✓	✓
2 mil (50 µm) Polyester	XF-446	Gloss White	1 mil (25 µm) Acrylic	✓	✓	100 hrs at 302 °F (150°C) <i>Operating:</i> -40 to 400 °F (-40 to 204 °C)	✓	✓

** Recommended thermal transfer ribbons included on technical data sheets.

For additional technical information, please contact us at **603.352.1415** or info@polyonics.com

July 2021

Polyonics World Headquarters

28 Industrial Park Drive
Westmoreland, NH 03467 U.S.A.
Ph: 603.352.1415
Fax: 603.352.1936
Email: info@polyonics.com

Asia Email: infoasia@polyonics.com

polyonics.com

